



- ▶ Access and control four multi-head computers
- ▶ Resolutions up to 3840×2160 @ 30Hz
- ▶ Switch using front panel buttons, keyboard hot keys, or RS-232 commands
- ▶ Supports all USB 1.1 or USB 2.0 devices
- ▶ Supports analog audio

Features and Benefits

- Quad-head or dual-head video input
- Resolutions up to 3840×2160 @30 Hz
- HDMI 1.4a compliant
- Full USB keyboard and mouse emulation to all computers provides switching without interruption
- Independent switching of KVM, peripheral USB devices, and audio
- Unit can be controlled using front panel push buttons, keyboard hot key commands, or RS-232 commands from an external controller
- Front panel LEDs indicate the active computer connection
- Can be used with any major operating system: Windows, Linux, MAC OS
- EDID pass-through enables smooth and efficient switching

Product Overview

The MultiVideo HDMI dual-head or quad-head switch can be used in any application where an operator requires access to up to four multi-head HDMI video sources. It can be used for digital signage, audio-visual presentations, control rooms, education, and many other applications.

MultiVideo HDMI supports video resolutions up to 3840×2160 @30Hz. Switching computers can be accomplished by pressing buttons on the front panel, or by issuing keyboard hot keys or RS232 commands. The front panel LEDs indicate the port number of the currently selected computer.

Keyboard and mouse uses emulation to provide the best possible switching experience. USB 2.0 devices are passed through directly without emulation at high speed. Stereo analog audio is also switched without any adulteration of the signal. The USB 2.0 devices or the audio can be switched separately from the video. Video, keyboard, and mouse are always switches together.

Monitor EDID is passed to video sources to ensure optimum output resolution and smooth switching.

Typical Application



Installation Installing the MultiVideo HDMI is just a matter of connecting the cables.

1. Video is connected to computers with HDMI male-to-male cables. The display also connects with a HDMI male-to-male cable.
2. Computer USB connects to computers with standard USB A-B cables.
3. USB keyboard and mouse connect to dedicated ports on the switch. USB 2.0 devices such as printers or scanners also connect directly to the unit.
4. You can use audio over HDMI or connect analog audio with standard 3.5mm cables.
5. The power adapter goes to the DC barrel jack.
6. Optionally connect a RS232 male-female cable to a PC or other device for external control.

The unit can be rack mounted in a 19" rack if so desired.

Operation To switch all devices (KVM, USB 2.0, and audio), the keyboard hot-key sequence is: Ctrl key twice, followed by m, then the port number 1-4, and finally Enter. Other similar sequences can be used to switch only KVM, only USB2.0, or only audio. You can also use a command or front panel switches to go to the next or previous port.

Specifications

Dimensions (W x D x H)	Dual-Head: 12.8" x 6.0" x 3.0" (325mm x 152mm x 76mm) Quad-Head: 12.8" x 6.0" x 4.5" (325mm x 152mm x 114mm)
Weight	Dual-Head: 4.0 lb (1.8 kg) Quad-Head: 5.75 lb (2.6 kg)
Power	External adapter, 100-240 VAC, 5VDC, 4A, 20W
Max. resolution	3840x2160 @30Hz (HDMI 1.4a)
Bandwidth	10.2 Gbps
Distance	16 feet (5.0m) each side
Function:	Connector:
Video in	8x (dual) / 16x (quad) DP female
Video out	2x (dual) / 4 (quad) DP female
USB 2.0/1.1 host	2x (dual) / 4 (quad) HDMI female
USB2.0/1.1 device	4x USB Type B receptacle
Keyboard/mouse	2x USB Type A receptacle
Audio in/out	2x USB Type A receptacle
Serial RS232	5x 3.5mm stereo jack
Power	1x DB9 female
Controls and status	1x 5V DC barrel jack
	Port selection by: 2x front panel push-button Keyboard hotkey sequence Serial port data commands Green LEDs 1-4: Port select status
RS-232	9600 baud
Environment	Operating temp: 23°F – 95°F (-5°C – 35°C) Storage temp: -4°F – 185°F (-20°C – 85°C) Rel. humidity: 5% – 95%, non-condensing
Approvals	UL, CE, RoHS compliant

Part numbers

MDM-4T2HD-A1	1X4 HDMI KVM Switch, Dual-head
MDM-4T4HD-A1	1X4 HDMI KVM Switch, Quad-head
CAB-HDMIMM006	HDMI cable, M/M, 6ft (2.0m)
CAB-USBMM006	USB-AB cable, M/M, 6ft (2.0m)
CAB-SPMM006	Audio cable, 3.5mm M/M, 6ft (2.0m)
CAB-D9MF006	Serial cable, DB9 M/F, 6ft (2.0 m)



Rear view of MultiVideo quad model

WWW.ROSE.COM ▪ **sales@rose.com** ▪ **(800) 333-9343**

Rose Electronics ▪ 10707 Stancliff Road ▪ Houston, Texas 77099
Rose USA (281) 933-7673 ▪ Rose Europe +49 (0) 2454 969442
Rose Asia +65 6324 2322 ▪ Rose Australia +61 (0) 421 247083

datasheet-multivideo-hdmi-2018-04-21

 **ROSE**
ELECTRONICS
WWW.ROSE.COM